



Offshorerist - 35 mm

**FLEXI-OXSP535-41/101-5**



Flexi Riste A/S  
Hjejlevej 10  
DK - 7480 Vildbjerg  
(+45) 97 13 32 11  
mail@flexiriste.no  
www.flexiriste.no

## Egenskaper

Materiale .....	S355JR
Overflatebehandling .....	Varmgalvanisert iht. DIN EN ISO 1461
Sklisikkerhetsklasse .....	R12
	15 mm kuglebestandig
Bærerib høyde .....	35 mm
Bærerib tykkelse .....	5 mm
Bærerib avstand (c/c) .....	41,46 mm
Tverrib (smijern) .....	Ø8 mm
Rundjern .....	Ø7 mm
Tverrib avstand (c/c) .....	101,6 mm
Maskestørrelse .....	41 x 101 mm
Iht. norm .....	MOTS-31
	EN ISO 14122
Punktlast .....	1,5 kN
Punktflate .....	200 x 200 mm
Fritt spenn .....	1.335 mm
Nedbøyning .....	4,0 mm
Flatelast .....	7,4 kN/m <sup>2</sup>
Fritt spenn .....	1.335 mm
Nedbøyning .....	4,0 mm
Flatelast .....	4 kN/m <sup>2</sup>
Fritt spenn .....	1.550 mm
Nedbøyning .....	4,0 mm
Festebeslag .....	B117K

*Vi leverer alle festebeslag i varmgalvanisert stål, rustfritt stål AISI304 og rustfritt stål AISI316*

